



LAWRENCE
LIVERMORE
NATIONAL
LABORATORY

Improvements in Modeling Au Sphere Non-LTE X-ray Emission

M. D. Rosen, H. A. Scott, L. J. Suter, S. B.
Hansen

November 10, 2008

APS/DPP
Dallas, TX, United States
November 17, 2008 through November 20, 2008

Disclaimer

This document was prepared as an account of work sponsored by an agency of the United States government. Neither the United States government nor Lawrence Livermore National Security, LLC, nor any of their employees makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States government or Lawrence Livermore National Security, LLC. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States government or Lawrence Livermore National Security, LLC, and shall not be used for advertising or product endorsement purposes.

Improvements in Modeling Au Sphere Non-LTE X-ray Emission

Presented to:

APS/DPP

Dallas, TX



**Mordecai D. (“Mordy”) Rosen, Howard A. Scott,
Laurance J. Suter, and Stephanie B. Hansen**

Lawrence Livermore National Laboratory

November 17, 2008

This work was performed under the auspices of the U.S. Department of Energy by
Lawrence Livermore National Laboratory under Contract DE-AC52-07NA27344.

Lawrence Livermore National Laboratory, P.O. Box 808, Livermore, CA 94551-0808

UCRL-PRES-xxxxxx

Abstract



We've previously reported* on experiments at the Omega laser at URLLE, in which 1.0 mm in diameter, Au coated, spheres, were illuminated at either 10^{14} W/ cm² (10 kJ / 3 ns) or at 10^{15} W/ cm² (30 kJ / 1 ns).

Spectral information on the 1 keV thermal x-rays, as well as the multi-keV M-band were obtained.

We compared a variety of non-LTE atomic physics packages to this data with varying degrees of success. In this paper we broaden the scope of the investigation, and compare the data to newer models:

- 1) An improved Detailed Configuration Accounting (DCA) method.
- 2) This model involves adjustments to the standard XSN non-LTE model which lead to a better match of coronal emission as calculated by XSN to that calculated by SCRAM, a more sophisticated stand-alone model.

We show some improvements in the agreement with Omega data when using either of these new approaches.

* E. Dewald, M. D. Rosen, et al Physics of Plasmas **15**, 072706 (2008).



Summary of new models' performance

1) Omega Au 1-D sphere NLTE output analysis:

- Sub keV (\sim thermal) emission:
 - Good match to data for both models.
- M band:
 - @ 1E15 / 1 ns
 - **DCA** M band \sim 2x too high
 - **XSNLJS** M band \sim 2x too low
 - @ 1E14 / 3 ns
 - **DCA** M band \sim 3x too high
 - **XSNLJS** M band \sim OK

2) Implications for NIF point design 2-D hohlraum (vs. XSN):

- Both of these newer models give a few % higher T_r .
- This is consistent with their \sim 10% higher conversion efficiency in Omega Au spheres vs. XSN

We are testing 2 new non-LTE atomic models



1) **DCA:**

- Detailed Configuration Accounting
- PI is Howard Scott

2) **XSNLJS:**

- A judiciously chosen “set of knobs” that adjust various excitation rates within the context of our “standard” XSN average atom model.
- These “knob settings” were chosen by Larry J. Suter in order to match the emissivity of Au at $0.2 n_{\text{crit}}$ for 1-3 keV as predicted by SCRAM, a very detailed atomic physics code due to S. Hansen et al.
- Our previous studies were with standard XSN and with SCA.

Au Omega sphere allows for 1-D simulations and for comparison to data



$T_e(x,t)$


(via Thomson Scattering)

$E_{\text{Laser absorbed}}(t)$

(via the FABS diagnostic)

$E_{\text{x-ray}}(h\nu, x, t)$

(via Dante & other diagnostics)




1-D simulations allow
for 400-zone runs:


very well resolved
conversion efficiency
layer

“Typical” comparison of simulation with data ☐

(@ 10^{15} W/cm²)



Au Simulation
30 KJ / 1 ns 10^{15} W/cm²



Data

SCA M-band ~20% too high

DCA: comparison of simulation with data (@ 10^{15} W/cm^2) : M band is $\sim 1.7\text{x}$ too high



Total X-rays




M-band



QuickTime™ and a
TIFF (LZW) decompressor
are needed to see this picture.

1000

500



Au DCA Simulation
30 KJ / 1 ns 10^{15} W/cm^2

Data

XSNLJS: comparison of simulation with data ☐

(@ 10^{15} W/cm²) : M band is ~ 0.6x too low



Total X-rays




QuickTime™ and a
TIFF (LZW) decompressor
are needed to see this picture.

M-band →

1000

500




Au XSNLJS Simulation

30 KJ / 1 ns 10^{15} W/cm²

Data

The general vanilla XSN spectral behavior vs. Target Material is modeled well (@ 10^{15} W/cm²)



Au, U, CT XSN (no Auger) Simulations

Data

30 KJ / 1 ns 10^{15} W/cm² at $t=0.9$ ns

DCA has trouble with the spectral shape for Au (@ 10^{15} W/cm²) : High M - band




GW/
sr.eV

1.0

0.5

QuickTime™ and a
TIFF (LZW) decompressor
are needed to see this picture.



Au, DCA Simulation

Data

30 KJ / 1 ns 10^{15} W/cm² at t= 0.9 ns

XSNLJS has trouble with Au spectral shape (@ 10^{15} W/cm²) : High Sub keV & Low M - band




GW/
sr.eV

1.0

0.5

QuickTime™ and a
TIFF (LZW) decompressor
are needed to see this picture.



Au, XSNLJS Simulation

Data



30 KJ / 1 ns 10^{15} W/cm² at t= 0.9 ns

Summary: 10^{15} W/cm²



| | Total | M-Band |
|-----------------------------------|-------|--------|
| Data (GW/Sr @ peak) | 1600 | 400 |
| Model (Type : Flux limit / Auger) | | |
| XSN 0.15 / - | 1600 | 300 |
| XSNLJS 0.15 / + | 1700 | 250 |
| DCA 0.15 / + | 1600 | 630 |

“Typical” vanilla XSN comparison of simulation with data \square (@ 10^{14} W/cm²)



XSN Au Simulation
10 KJ / 3 ns 10^{14} W/cm²

XSN M-band ~ 2 x too low early in the pulse
SCA M-band > 2 x too high throughout the pulse

Data

DCA0508 comparison of simulation with data ☐ (@ 10^{14} W/cm²)- near perfection!



400


Total X-rays



M-band



10



Au Simulation DCA 0508

10 KJ / 3 ns 10^{14} W/cm²

Data

DCA0908 comparison of simulation with data ☐ (@ 10^{14} W/cm²)- now M band is 3x too high!



400


Total X-rays



QuickTime™ and a
TIFF (LZW) decompressor
are needed to see this picture.

M-band

10



Au Simulation DCA 0908

10 KJ / 3 ns 10^{14} W/cm²

Data

XSNLJS comparison of simulation with data ☐

(@ 10^{14} W/cm²)- ~ same as XSN!



400


Total X-rays



M-band

10

QuickTime™ and a
Truevision™ decompressor
are needed to see this picture.




Au Simulation XSNLJS


10 KJ / 3 ns 10^{14} W/cm²

Data

The general spectral behavior vs. Target Material is modeled well (@ 10^{14} W/cm 2)



t=3 ns au, CT blue , red noj
plot hbin24 histoen4 color=blue



Au, CT XSN Simulations

Data

10 KJ / 3 ns 10^{14} W/cm 2 at $t=2.9$ ns


The Au sub keV spectral shape is modeled especially well by **DCA**(@ 10^{14} W/cm²)



GW/
sr.eV

0.5

QuickTime™ and a
TIFF (LZW) decompressor
are needed to see this picture.



Au, **DCA** Simulation

Data

10 KJ / 3 ns 10^{14} W/cm² at t= 2.9 ns


The Au spectral behavior is modeled ~ OK by **XSNLJS** (@ 10^{14} W/cm²)



GW/
sr.eV

0.5

QuickTime™ and a
TIFF (LZW) decompressor
are needed to see this picture.



Au, **XSNLJS** Simulation

Data

10 KJ / 3 ns 10^{14} W/cm² at t= 2.9 ns

Summary: 10^{14} W/cm²



| | Total | M-Band |
|-----------------------------------|-------|--------|
| Data (GW/Sr @ peak) | 300 | 3 |
| Model (Type : Flux limit / Auger) | | |
| XSN 0.15 / - | 300 | 2 |
| XSNLJS 0.15 / + | 300 | 4 |
| DCA 0.15 / + | 300 | 12 |

NIF 2-D hohlraum point design sensitivities



- **XSN: Auger / Di-electronic effects:**
 - Lowers $Z\text{-bar}$ in Au corona by $\sim 10\%$.
 - Lowers T_e in Au corona by $\sim 10\%$.
 - Raises T_r in hohlraum by ~ 5 eV or “Dante signal” by 7%
- **DCA, XSNLJS:**
 - Rise in T_r consistent with their higher conversion efficiency as seen in the Omega Au Sphere simulations
 - Running laser Power @ 0.9x can \sim reproduce T_r as seen in XSN

NIF 2-D hohlraum point design sensitivities



- XSN: dotted line
- XSNLJS
 - Upper: full power
 - Lower: 90% power
- DCA
 - Upper: full power
 - Lower: 90% power

QuickTime™ and a
TIFF (LZW) decompressor
are needed to see this picture.

Acknowledgments



- **Atomic Models**
 - E. Alley, B. Wilson, P. Springer, J. Castor, J. Albritton
- **Data**
 - E. DeWald, S. Glenzer, S. Ross, D. Froula, P. Neumayer, N. Landen, S. Regan
- **Computational Issues**
 - J. Harte, G. Zimmerman, D. Bailey, D. Callahan, O. Jones
- **Support & Encouragement**
 - C. Verdon, E. Moses, B. MacGowan